

SolSwitch™-2000

An Advanced IP PBX for Single-Site or Multi-Site Enterprises



- Perfect for businesses requiring redundancy
- Thrives in multi-site offices
- Up to 1,000 users
- Dual power supply & hot-swap HDD
- Easy to use administrative web-portal
- SIP-ready

Overview

The SolSwitch-2000 is capable of supporting large multi-site operations. A next generation IP based phone system, the SolSwitch comes with a set of basic features as well as the option of upgrading to advanced features or the carrier platform. Includes dual power supplies and hot-swappable HDDs.

This 2U rackmount appliance can support 1,000 users and has no extension or voicemail limit. Compatible with a large range of devices and services, the SS2000 gives you total control over how your phone system functions.

SIP-ready and fully compliant to the SIP standard, the SolSwitch-2000 has the ability to integrate with analog lines and/or devices. All SolSwitch models come with a 2-year warranty with the option to purchase a 5-year extended warranty.

Includes SIP Service

Every SolSwitch-2000 comes with the following services:

- 1 SIP Channel (30 days free)*
- 1 DID (30 days free)**
- Free telephone guidance
- 80 concurrent call license
- 2-year hardware warranty

SIP Compatibility

- Adtran TotalAccess, TotalAccessE, and NetVanta series
- AudioCodes Mediant Series SBCs and Gateways
- Algo 8180
- Mitel 6755i, 6757i, 6863i, 6865i, 6867i, 6869i, 9143i
- Cisco SPA-112, SPA-122, SPA-2102, SPA-504G, SPA-509G, SPA-514G, SPA-525G, SPA-922, SPA-942
- CounterPath Bria and any SIP compatible softphone
- Panasonic UT123, UT133, UT136, TGP600 (cordless)
- Polycom SoundPoint IP, 335, 450, 550, 560, 650, 670, VVX-300, VVX-310, VVX-400, VVX-410, VVX-500, VVX-1500, SoundStation 5000, 6000, 7000
- Grandstream HT701, HT702, HT704, HT802, DP715
- Yealink T26, T28, T34

In the Box

- SolSwitch-2000
- 2 x Power Cables
- 2 x 6-foot Cat5e Patch Cables

Hardware Specifications

- CPU: Intel Xeon E5 6 Cores @ 2.2Ghz
- RAM: 16GB
- Storage (Hot-Swap): 2 x 1TB (RAID 1)
- USB 2.0 port
- Ethernet: 2 x RJ-45 (Expandable to 6)
- Power Supply (Hot-Swap): 740W Redundant
- Dimensions: 25.5" x 17.2" x 3.5"
(W x D x H)

* Option to keep service for \$22.95/month per SIP channel. Contact Sunwire for more details.

** Option to keep DID or purchase additional DIDs for \$2.00/month per DID. Contact Sunwire for more details.