

SolSwitch™-1000

For Single-site or Multi-site Organizations



- Up to 250 users
- Intel Xeon E3
- Redundancy upgrades available
- Ideal for multi-site environments

Overview

The SolSwitch-1000 is ideal for supporting medium-sized single site businesses or larger multi-site organizations. An IP-based phone system, all SolSwitch models come with a set of standard phone system features with the option of upgrading to the Advanced Features.

This 1U rackmount supports up to 250 users, has no extension or voicemail limit and is compatible with a wide-range of devices and services – giving you total control over the functionality of your telephone system.

SIP-ready and fully compliant to the SIP standard, the SolSwitch has the ability to integrate with analog lines and/or devices. All SolSwitch models come with a 2-year warranty with the option to purchase a 5-year extended warranty.

In the Box

- SolSwitch-1000
- 1 x Power Cables
- 2 x 6' Cat5e Patch Cables

SIP Compatibility

- Adtran Total Access Series, Total Access E Series, Net Vanta Series
- AudioCodes Mediant Series SBCs and Gateways
- Algo 8180
- Cisco SPA-122, SPA-122, SPA2102, SPA-504G, SPA-509G, SPA-514G, SPA-525G, SPA-922, SPA-942
- Grandstream HT701, HT702, HT704, HT802, DP715
- Mitel 6755i, 6757i, 6863i, 6865i, 6867i, 6869i, 9143i
- Panasonic UT123, UT133, UT136, TGP600 (cordless)
- Polycom SoundPoint IP-335, IP-450, IP-550, IP-560, IP-650, IP-670, VVX-300, VVX-310, VVX-400, VVX-410, VVX-500, VVX-1500, SoundStation 5000, SoundStation 6000, SoundStation 7000

Hardware Specifications

- CPU: 2 x Intel Xeon E3 3.1Ghz
- RAM: 8GB
- Storage: 2 x 500GB (RAID 1)
- Ethernet: 2 x RJ-45
- Power Supply: 260W
- Dimensions: 16.8" x 14" x 1.7"
(W x D x H)